



LED Tubular Striplight

Features

- Extremely energy saving with low power consumption
- Ideal retrofit of traditional incandescent striplights
- Direct AC input with integrated driver
- No mercury and hazardous substances
- PC housing
- 120V is available on request
- Good color rendition, Ra ≥ 80

EUROPE


LINE VOLTAGE LAMP



T9 S14s Base




T9 S14d Base




T8 S15 Base



T12 S19 Base



T9 S14s Base




T9 S14d Base



T8 S15 Base



T12 S19 Base



Model	Voltage	Wattage	Base	Beam Angle	Diameter D	Length L	Color Temp	Lumen	
LED TP S14s T9 5W	220 - 240V	5W	S14s	270°	Ø30mm	300mm	2700K	450lm	F
LED TP S14s T9 8W	220 - 240V	8W	S14s	270°	Ø30mm	500mm	2700K	750lm	F
LED TP S14s T9 5W DIM	220 - 240V	5W	S14s	270°	Ø30mm	300mm	2700K	450lm	F
LED TP S14s T9 8W DIM	220 - 240V	8W	S14s	270°	Ø30mm	500mm	2700K	750lm	F
LED TP S14d T9 5W	220 - 240V	5W	S14d	270°	Ø30mm	300mm	2700K	450lm	F
LED TP S14d T9 8W	220 - 240V	8W	S14d	270°	Ø30mm	500mm	2700K	750lm	F
LED TP S14d T9 5W DIM	220 - 240V	5W	S14d	270°	Ø30mm	300mm	2700K	450lm	F
LED TP S14d T9 8W DIM	220 - 240V	8W	S14d	270°	Ø30mm	500mm	2700K	750lm	F
LED TP S15 T8 4W	220 - 240V	4W	S15	300°	Ø26mm	221mm	2700K	350lm	F
LED TP S15 T8 6W	220 - 240V	6W	S15	300°	Ø26mm	284mm	2700K	550lm	F
LED TP S15 T8 4W DIM	220 - 240V	4W	S15	300°	Ø26mm	221mm	2700K	350lm	F
LED TP S15 T8 6W DIM	220 - 240V	6W	S15	300°	Ø26mm	284mm	2700K	550lm	F
LED TP S19 T12 7W	220 - 240V	7W	S19	300°	Ø38mm	310mm	2700K	600lm	F
LED TP S19 T12 7W DIM	220 - 240V	7W	S19	300°	Ø38mm	310mm	2700K	600lm	F

T9 S14s Base




5W ~ 35W
8W ~ 60W

T9 S14d Base



5W ~ 35W
8W ~ 60W

T8 S15 Base /
T12 S19 Base

4W ~ 30W
6W ~ 60W
7W ~ 60W