




Model	Wattage	Voltage	Color	Color Temp	CRI	Lumen	Angle	Length	Type	Efficacy	Power factor
LED F8T8/830/G/600	8W	220-240V	Warm White	3000K	≥80	720lm	280°	600mm	Type B	90lm/W	0.5
LED F8T8/840/G/600	8W	220-240V	Neutral White	4000K	≥80	760lm	280°	600mm	Type B	95lm/W	0.5
LED F8T8/865/G/600	8W	220-240V	Daylight	6500K	≥80	800lm	280°	600mm	Type B	100lm/W	0.5
LED F9T8/830/G/600	9W	220-240V	Warm White	3000K	≥80	810lm	280°	600mm	Type B	90lm/W	0.5
LED F9T8/840/G/600	9W	220-240V	Neutral White	4000K	≥80	855lm	280°	600mm	Type B	95lm/W	0.5
LED F9T8/865/G/600	9W	220-240V	Daylight	6500K	≥80	900lm	280°	600mm	Type B	100lm/W	0.5
LED F10T8/830/G/600	10W	220-240V	Warm White	3000K	≥80	900lm	280°	600mm	Type B	90lm/W	0.5
LED F10T8/840/G/600	10W	220-240V	Neutral White	4000K	≥80	950lm	280°	600mm	Type B	95lm/W	0.5
LED F10T8/865/G/600	10W	220-240V	Daylight	6500K	≥80	1000lm	280°	600mm	Type B	100lm/W	0.5
LED F12T8/830/G/900	12W	220-240V	Warm White	3000K	≥80	1080lm	280°	900mm	Type B	90lm/W	0.5
LED F12T8/840/G/900	12W	220-240V	Neutral White	4000K	≥80	1140lm	280°	900mm	Type B	95lm/W	0.5
LED F12T8/865/G/900	12W	220-240V	Daylight	6500K	≥80	1200lm	280°	900mm	Type B	100lm/W	0.5
LED F16T8/830/G/1200	16W	220-240V	Warm White	3000K	≥80	1440lm	280°	1200mm	Type B	90lm/W	0.5
LED F16T8/840/G/1200	16W	220-240V	Neutral White	4000K	≥80	1520lm	280°	1200mm	Type B	95lm/W	0.5
LED F16T8/865/G/1200	16W	220-240V	Daylight	6500K	≥80	1600lm	280°	1200mm	Type B	100lm/W	0.5
LED F18T8/830/G/1200	18W	220-240V	Warm White	3000K	≥80	1620lm	280°	1200mm	Type B	90lm/W	0.5
LED F18T8/840/G/1200	18W	220-240V	Neutral White	4000K	≥80	1710lm	280°	1200mm	Type B	95lm/W	0.5
LED F18T8/865/G/1200	18W	220-240V	Daylight	6500K	≥80	1800lm	280°	1200mm	Type B	100lm/W	0.5
LED F20T8/830/G/1200	20W	220-240V	Warm White	3000K	≥80	1800lm	280°	1200mm	Type B	90lm/W	0.5
LED F20T8/840/G/1200	20W	220-240V	Neutral White	4000K	≥80	1900lm	280°	1200mm	Type B	95lm/W	0.5
LED F20T8/865/G/1200	20W	220-240V	Daylight	6500K	≥80	2000lm	280°	1200mm	Type B	100lm/W	0.5
LED F22T8/830/G/1200	22W	220-240V	Warm White	3000K	≥80	1980lm	280°	1200mm	Type B	90lm/W	0.5
LED F22T8/840/G/1200	22W	220-240V	Neutral White	4000K	≥80	2090lm	280°	1200mm	Type B	95lm/W	0.5
LED F22T8/865/G/1200	22W	220-240V	Daylight	6500K	≥80	2200lm	280°	1200mm	Type B	100lm/W	0.5

Features


- Energy saving with low power consumption
- Direct retrofit for magnetic ballast circuit
- No mercury and hazardous substances

Wiring

For direct retrofit in CCG circuit replace LED tube and take out starter




For direct connection with AC



Installation Guide

For direct retrofit in CCG circuit, replace LED tube and take out starter



For direct connection with AC

