EU Basic




Model	Wattage	Voltage	Color	Color Temp	CRI	Lumen	Angle	Length	Type	Efficacy	Power factor
LED F9T8/830/G/600	9W	220-240V	Warm White	3000K	≥80	810lm	280°	600mm	Type A	90lm/W	0.5
LED F9T8/840/G/600	9W	220-240V	Neutral White	4000K	≥80	855lm	280°	600mm	Type A	95lm/W	0.5
LED F9T8/865/G/600	9W	220-240V	Daylight	6500K	≥80	900lm	280°	600mm	Type A	100lm/W	0.5
LED F10T8/830/G/600	10W	220-240V	Warm White	3000K	≥80	900lm	280°	600mm	Type A	90lm/W	0.5
LED F10T8/840/G/600	10W	220-240V	Neutral White	4000K	≥80	950lm	280°	600mm	Type A	95lm/W	0.5
LED F10T8/865/G/600	10W	220-240V	Daylight	6500K	≥80	1000lm	280°	600mm	Type A	100lm/W	0.5
LED F14T8/830/G/900	14W	220-240V	Warm White	3000K	≥80	1260lm	280°	900mm	Type A	90lm/W	0.5
LED F14T8/840/G/900	14W	220-240V	Neutral White	4000K	≥80	1330lm	280°	900mm	Type A	95lm/W	0.5
LED F14T8/865/G/900	14W	220-240V	Daylight	6500K	≥80	1400lm	280°	900mm	Type A	100lm/W	0.5
LED F18T8/830/G/1200	18W	220-240V	Warm White	3000K	≥80	1620lm	280°	1200mm	Type A	90lm/W	0.5
LED F18T8/840/G/1200	18W	220-240V	Neutral White	4000K	≥80	1710lm	280°	1200mm	Type A	95lm/W	0.5
LED F18T8/865/G/1200	18W	220-240V	Daylight	6500K	≥80	1800lm	280°	1200mm	Type A	100lm/W	0.5
LED F20T8/830/G/1200	20W	220-240V	Warm White	3000K	≥80	1800lm	280°	1200mm	Type A	90lm/W	0.5
LED F20T8/840/G/1200	20W	220-240V	Neutral White	4000K	≥80	1900lm	280°	1200mm	Type A	95lm/W	0.5
LED F20T8/865/G/1200	20W	220-240V	Daylight	6500K	≥80	2000lm	280°	1200mm	Type A	100lm/W	0.5
LED F22T8/830/G/1200	22W	220-240V	Warm White	3000K	≥80	1980lm	280°	1200mm	Type A	90lm/W	0.5
LED F22T8/840/G/1200	22W	220-240V	Neutral White	4000K	≥80	2090lm	280°	1200mm	Type A	95lm/W	0.5
LED F22T8/865/G/1200	22W	220-240V	Daylight	6500K	≥80	2200lm	280°	1200mm	Type A	100lm/W	0.5
LED F22T8/830/G/1500	22W	220-240V	Warm White	3000K	≥80	1980lm	280°	1500mm	Type A	90lm/W	0.5
LED F22T8/840/G/1500	22W	220-240V	Neutral White	4000K	≥80	2090lm	280°	1500mm	Type A	95lm/W	0.5
LED F22T8/865/G/1500	22W	220-240V	Daylight	6500K	≥80	2200lm	280°	1500mm	Type A	100lm/W	0.5
LED F24T8/830/G/1500	24W	220-240V	Warm White	3000K	≥80	2160lm	280°	1500mm	Type A	90lm/W	0.5
LED F24T8/840/G/1500	24W	220-240V	Neutral White	4000K	≥80	2280lm	280°	1500mm	Type A	95lm/W	0.5
LED F24T8/865/G/1500	24W	220-240V	Daylight	6500K	≥80	2400lm	280°	1500mm	Type A	100lm/W	0.5

Features


- Energy saving with low power consumption
- No mercury and hazardous substances
- Direct retrofit for magnetic ballast circuit

Wiring

For direct retrofit in CCG circuit, replace LED tube and LED starter




For direct connection with AC



Installation Guide

For direct retrofit in CCG circuit, replace LED tube and LED starter



For direct connection with AC

