

Dimmable Filament-LED S14 120V

2W/4W


Features

- Extremely energy saving with low power consumption
- Full glass version ideal retrofit of traditional lamps with same appearance / performance / dimensions
- Overall light distribution
- CCT 4000K also available
- Good color rendition, Ra ≥80



Diagrams

Dimensions:



Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Standards



Applications



Technical Data	
Electrical	
Rated Wattage [W]	2W / 4W
Rated Voltage [V/Hz]	110-130Vac, 50/60Hz
Power Factor @120V	0.93
Input Current [mA] @120V	18 / 36
Model	
LED NA S14 FIL-2W-G CL DIM	2W
LED NA S14 FIL-4W-G CL DIM	4W
Luminous Flux [lm]	
2W	170lm @2700K
4W	350lm @2700K
Performance	
SDCM	<6
Estimated Yearly Energy Cost [\$USD]	0.24 / 0.48
Luminous Efficacy [lm/W]	85-88
Color Rendering Index [Ra]	≥80
Color Maintenance [hr]	>6000
Luminous Intensity Distribution [°]	360
Life [Yrs] (based on 3hrs/day)	14
Lumen Maintenance at 6000hrs	>0.8
Rapid Cycle Stress	>15,000 cycles
Start Time [sec]	<0.5
LED Failure	<5%
Mechanical	
Diameter D [in]	Φ1.77
Height H [in]	3.35
Base	E26
Material	Glass

Standard Compliance		
ANSI		UL8750, UL1993, C82.77-2002, C78.377-2008
FCC		FCC CFR Part 15, FCC CFR Part 18
Mercury Content [mg]		0.0
Energy Star		Y
Other		
Dimmable [Y/N]		Y
Operation Temperature		-20°C ~ 50°C
Storage Temperature		-10°C ~ 30°C