

LED COB PAR36/ES111

6W/8W/10W


Features

- Extremely energy saving with low power consumption
- Ideal retrofit solution for PAR36/ES111 halogen lighting, same glass body finishing and identical size
- No mercury and hazardous substances
- Good color rendition, Ra ≥ 80



Diagrams

Dimensions:




Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Standards



Applications



Technical Data		
Type of Light Source		
Lighting Technology Used	LED	
Non-directional or Directional [NDLS/DLS]	DLS	
Mains or Non-mains [MLS/NMLS]	MLS	
Connected Light Source	No	
Color tunable light source	No	
Envelop [No/Second/Non-Clear]	No	
High Luminance Light Source	No	
Anti-glare Shield	No	
Electrical		
Rated Wattage [W]	6W / 8W / 10W	
On-mode Power [W]	6W / 8W / 10W	
Standby Power [W]	N/A	
Networked Standby Power [W]	N/A	
Rated Voltage [V/Hz]	220-240Vac, 50/60Hz	
Power Factor @230V	0.5	
Input Current [mA] @230V	52 / 70 / 87	
LED	COB	
Model		
LED PAR36/ES111 COB-6W	6W	
LED PAR36/ES111 COB-8W	8W	
LED PAR36/ES111 COB-10W	10W	
Luminous Flux (Useful Luminous Flux) [lm]		
6W	455lm (390lm) @3000K	
	470lm (400lm) @4000K	
	490lm (410lm) @6500K	
8W	700lm (600lm) @3000K	
	720lm (610lm) @4000K	

10W	740lm (630lm) @6500K
	825lm (700lm) @3000K
	850lm (720lm) @4000K
	875lm (750lm) @6500K
Peak Luminous Intensity [cd]	
6W 30°	1131@3000K / 1141@4000K / 1151@6500K
8W 30°	1190@3000K / 1200@4000K / 1210@6500K
10W 30°	1228@3000K / 1238@4000K / 1248@6500K
6W 60°	1161@3000K / 1171@4000K / 1181@6500K
8W 60°	1250@3000K / 1260@4000K / 1270@6500K
10W 60°	1288@3000K / 1298@4000K / 1308@6500K
Performance	
SCDM	<6
Chromaticity coordinates [x, y]	0.44, 0.403@3000K / 0.38,0.38@4000K / 0.312, 0.335@6500K
Efficacy [lm/W]	65-68
Color Rendering Index [Ra]	≥80
R9 colour rendering index value	2
Beam Angle [°]	30 / 60
Rated Life, Ta@25°C [hrs]	25,000
Lamp Survival Factor	0.9
Lumen Maintenance	0.96
Number of Switching Cycles Before Failure	>15,000
Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	0.5
Flicker Metric [Pst LM]	1
Stroboscopic Effect Metric [SVM]	0.4
Mechanical	
Diameter D [mm]	Φ111
Height H [mm]	70
Base	GU10
Material	Glass with special IR dichroic coating
Standard Compliance	
CE-LVD	EN62560
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
CE-EMF	EN62493
Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	F
Other	
Dimmable [Yes/Only with specific dimmers/No]	No
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Claim of Equivalent Power, 6W [W]	58W
Claim of Equivalent Power, 8W [W]	86W
Claim of Equivalent Power, 10W [W]	102W
Energy Consumption in on-mode [kWh/1000h]	6kWh / 8kWh / 10kWh