

LED Spotlight NS124E-126E

12Wx1/12Wx2/12Wx3


Features

- 12Wx1 / 12Wx2 / 12Wx3 LED spotlight
- Adjustable tilting angle of 0°-15° vertically and 350° horizontally
- Dimmable as option
- Color Rendering Index: ≥80
- Special color spectrum for aquarium, agriculture and food display, available on request



Diagrams

Dimensions:



Standards



IP20

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Applications


Shopping mall


Hotel


Supermarket


Restaurant


Arena


Gallery


Museum

Technical Data	
Electrical	
Rated Wattage [W]	12Wx1 / 12Wx2 / 12Wx3
Rated Voltage [V/Hz]	220-240Vac, 50/60Hz
Power Factor @230V	0.99
Input Current [mA] @230V	53 / 105 / 158
LED	COB
Model	
NS124E-12Wx1/8XX	12Wx1 (1 x COB 9W, 350mA, 27±1Vdc, 1260-1380lm)
NS125E-12Wx2/8XX	12Wx2 (2 x COB 9W, 350mA, 27±1Vdc, 1260-1380lm)
NS126E-12Wx3/8XX	12Wx3 (3 x COB 9W, 350mA, 27±1Vdc, 1260-1380lm)
Luminous Flux [lm]	
12Wx1	620lm @3000K
	650lm @4000K
	680lm @6500K
12Wx2	1240lm @3000K
	1300lm @4000K
	1360lm @6500K
12Wx3	1860lm @3000K
	1950lm @4000K
	2040lm @6500K
Performance	
SDCM	<6
Efficacy [lm/W]	52-57
Color Rendering Index [Ra]	≥80
Beam Angle [°]	15 / 24 / 38 / 60
Rated Life, Ta@25°C [hrs]	50,000
Lamp Survival Factor at 6000hrs	>0.9
Lumen Maintenance at 6000hrs	>0.8
Number of Switching Cycles Before Failure	>15,000
Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Mechanical	
Length L [mm]	100 / 180 / 260

Width W [mm]	100
Height H [mm]	110
Cut out [mm*mm]	80*80 / 80*160 / 80*240
Adjustable angle	15° tiltable and 350° rotatable
Material	Body: Anodised Steel
	Reflector: Anodised facettted aluminium
	Diffuser: Toughened glass
Standard Compliance	
CE-LVD	EN60598-1, EN60598-2-2
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
Mercury Content [mg]	0.0
Electrical Class	II
Other	
Dimmable [Y/N]	Optional
Operation Temperature	-10°C ~ 40°C
Storage Temperature	-20°C ~ 60°C