

LED T5 HO ECG

27W


Features

- Energy saving with low power consumption
- Smooth operation even at low temperatures
- No mercury and hazardous substances
- Full glass body
- Good color rendition, Ra ≥80




Diagrams

Dimensions:



Circuits:




- * Comply to EN62776
- Suitable for direct retrofit to 1x, 2x HO electronic ballast.
 - Compatible with T5 Fluorescent Emergency Kit.
 - Compatibility with 3x, 4x T5 fluo. HO electronic ballast depending on brand/model.

Standards



Applications



Technical Data	
Type of Light Source	
Lighting Technology Used	LED
Non-directional or Directional [NDLS/DLS]	NDLS
Mains or Non-mains [MLS/NMLS]	NMLS

Connected Light Source	No
Color tunable light source	No
Envelop [No/Second/Non-Clear]	No
High Luminance Light Source	No
Anti-glare Shield	No
Electrical	
Rated Wattage [W]	27W
On-mode Power [W]	27W
Standby Power [W]	N/A
Networked Standby Power [W]	N/A
Rated Voltage [V/Hz]	N/A
Power Factor @230V	0.95
Input Current [mA] @230V	124
Model	
LED F27T5/E/8XX/1200/HO/L	27W
LED F27T5/E/8XX/1500/HO/L	27W
Luminous Flux [lm]	
27W	3500lm @3000K
	3650lm @4000K
	3750lm @6500K
Performance	
SDCM	<6
Chromaticity coordinates [x, y]	0.44,0.403@3000K / 0.38,0.38@4000K / 0.312,0.335@6500K
Efficacy [lm/W]	130-139
Color Rendering Index [Ra]	≥80
R9 colour rendering index value	2
Beam Angle [°]	270
Rated Life, Ta@25°C [hrs]	40,000
Survival Factor	0.9
Lumen Maintenance Factor	0.96
Number of Switching Cycles Before Failure	>15,000
Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	N/A
Flicker Metric [Pst LM]	N/A
Stroboscopic Effect Metric [SVM]	N/A
Mechanical	
Diameter D [mm]	Φ16
Length L1 [mm]	1149 / 1449
Length L2 [mm]	1163 / 1463
Base	G5
Material	Glass
Standard Compliance	

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

CE-LVD	EN62776
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
CE-EMF	EN62493
Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	E
Other	
Dimmable [Yes/Only with specific dimmers/No]	No
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C
Claim of Equivalent Power, 27W [W]	54W / 49W
Energy Consumption in on-mode [kWh/1000h]	27kWh