

LED Batten NL300S 3CCT

26W


Features

- 26W LED Batten Light
- Suitable to use in factories, offices, banks, shopping centers, subways, schools and other places
- Selectable CCT via dip-switch
- Inventory cost saving
- Motion sensing
- Applicable in damp location
- Long average life 50000 hours
- Good color rendition, Ra ≥80




Diagrams

Dimensions:



Dip-switch:



Standards



Applications

Home

Office

Shopping mall

Hotel

Supermarket

Restaurant

Parking

School

Warehouse

Factory

Hospital

Gallery

Museum

Airport

Station

Technical Data	
Electrical	
Rated Wattage [W]	26W
Rated Voltage [V/Hz]	100-277Vac, 50/60Hz
Power Factor @120V	0.9
Input Current [mA] @120V	241
LED	SMD
Model	
NL300S-26W/8XX/3CCT	26W
Luminous Flux [lm]	
26W	2625lm @3000K-3500K-4000K
Performance	
SDCM	<6
Estimated Yearly Energy Cost [\$USD]	3.13
Luminous Efficacy [lm/W]	101
Color Rendering Index [Ra]	≥80
Color Maintenance [hr]	>6000
Luminous Intensity Distribution [°]	110
Life [Yrs] (based on 3hrs/day)	46
Lumen Maintenance at 6000hrs	>0.8
Rapid Cycle Stress	>15,000 cycles
Start Time [sec]	<0.5

LED Failure	<5%
Mechanical	
Length L [in]	46.5
Width W [in]	1.57
Height H [in]	2
Material	Steel and PC
Standard Compliance	
ANSI	UL8750, UL1993, UL1598, C82.77-2002, C78.377-2008
Mercury Content [mg]	0.0
Other	
Dimmable [Y/N]	N
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C