

LED Striplight

LED Striplight 2016 Super Slim

KANDOLite®



* Package Content : ~5m per reel

Features

- Extremely energy saving with low power consumption
- High brightness, multi-functional for linear decoration
- Long average life 30000 hours
- Good color rendition
- Low thermal output with no IR and harmful UV
- No mercury and hazardous substances
- Dimmable as option
- Color Rendering Index: ≥ 90

Materials / Finish

- Chips : SMD 2016

Installation / Mounting

- Easy to install with 3M adhesive tape, mounting brackets and profile

Standards

- Class III Electrical
- IP20, IP65, IP67
- UL, ETL

LED Driver Controllers



12V/24V
LED Driver



LED Dimmer
(With Remote
Control Device)



LED Manual
Controller



LED Remote
Controller

Connectors



2 Pin
Quick Connector



Strip-to-Wire



Strip-to-Strip



'I' Type
Fast Plug



'T' Type
Fast Plug



Wire-to-Wire
Fast Plug

Profiles




Surface
mounted




Unit in mm

* Extra profiles and accessories need to order separately.


IP Structures



IP20



IP65



IP67-R



Model	Voltage	Wattage	Color Temp	Lumen	PCB Width	Cutting Unit (12V / 24V)	No. of LEDs
LED 2016 7.2W 3.5-60 930	7.2W/m	12V / 24V DC	3000K	600lm/m	3.5mm	50mm/3LEDs / 100mm/6LEDs	60 pcs/m
LED 2016 7.2W 3.5-60 940	7.2W/m	12V / 24V DC	4000K	615lm/m	3.5mm	50mm/3LEDs / 100mm/6LEDs	60 pcs/m
LED 2016 7.2W 3.5-60 965	7.2W/m	12V / 24V DC	6500K	630lm/m	3.5mm	50mm/3LEDs / 100mm/6LEDs	60 pcs/m
LED 2016 14.4W 3.5-120 930	14.4W/m	24V DC	3000K	1200lm/m	3.5mm	50mm/6LEDs	120 pcs/m
LED 2016 14.4W 3.5-120 940	14.4W/m	24V DC	4000K	1230lm/m	3.5mm	50mm/6LEDs	120 pcs/m
LED 2016 14.4W 3.5-120 965	14.4W/m	24V DC	6500K	1260lm/m	3.5mm	50mm/6LEDs	120 pcs/m