

LED T8 支架 NL191A-192A
35W/42W



标准



应用



家居



办公室



购物中心



旅馆



超市



餐厅



停车场



学校



仓库



工厂



医院



艺术馆



博物馆



机场



铁路

技术参数

电参数

额定功率 [W]

35W / 42W

佑昌灯光器材有限公司

电话: (852) 2511 0022 传真: (852) 2511 0082 网址: www.prosperitylamps.com 电子邮件: info@prosperitylamps.com

额定电压 [V/Hz]	110-130Vac, 50/60Hz
功率因数 @120V	0.9
输入电流 [mA] @120V	324 / 389
LED	SMD
产品型号	
NL191A-42W/840	42W
NL192A-35W/840	35W
光通量 [lm]	
42W	3700lm @4000K
35W	3200lm @4000K
光效性能	
色容差	<6
预计每年能源支出 [\$USD]	4.22 / 5.06
光效 [lm/W]	88-91
显色指数 [Ra]	≥85
色效维持 [hr]	>6000
光度分布 [°]	120
寿命 [yrs] (每日使用3小时)	46
6000小时后, 光通维持率	>0.8
开关测试	>15,000 cycles
启动时间 [S]	<0.5
LED 失效率	<5%
尺寸和物料	
直径 D [in]	2.24 / 2.4
长度 L [in]	48
宽度 W [in]	5.39
物料	Powder coating iron housing and PC cover
标准	
ANSI	UL8750, UL1993, UL1598, C82.77-2002, C78.377-2008
汞含量 [mg]	0.0
其他	
调光 [Y/N]	N
工作温度	-20° C ~ 50° C
存储温度	-10° C ~ 30° C