

LED Ceiling Light NC151E - NC154E



Features

- 6W / 12W / 18W / 24W LED Ceiling Light
- Uniform distribution with opal diffuser
- Comfort glare-free light
- Good color rendition, Ra ≥ 80

Materials / Finish


- Body: Sheet steel with white finish
- Diffuser: Opaque acrylic

Installation / Mounting


- Suitable for surface mounting
- Integral gear unit allows quick and easy installation

Standards


- Designed and manufactured to comply international standard EN60598
- Class I Electrical
- IP 20



Lamp: LED 12W 3000K



(Unit : mm)	(D)	(H)
NC151E	$\varnothing 120$	x 32
NC152E	$\varnothing 170$	x 32
NC153E	$\varnothing 220$	x 32
NC154E	$\varnothing 300$	x 32



Model	Voltage	Luminaire Wattage	Luminaire Lumen	Color Temp	Beam Angle	Light Source Wattage	Light Source Lumen	Energy Efficiency Class
NC151E-6W/830	220 - 240V	6W	410lm	3000K	120°	5.4W	470lm	G
NC151E-6W/840	220 - 240V	6W	430lm	4000K	120°	5.4W	480lm	G
NC151E-6W/865	220 - 240V	6W	450lm	6500K	120°	5.4W	480lm	G
NC152E-12W/830	220 - 240V	12W	900lm	3000K	120°	10.8W	1120lm	F
NC152E-12W/840	220 - 240V	12W	950lm	4000K	120°	10.8W	1200lm	F
NC152E-12W/865	220 - 240V	12W	1000lm	6500K	120°	10.8W	1200lm	F
NC153E-18W/830	220 - 240V	18W	1450lm	3000K	120°	16.2W	1765lm	F
NC153E-18W/840	220 - 240V	18W	1550lm	4000K	120°	16.2W	1800lm	F
NC153E-18W/865	220 - 240V	18W	1650lm	6500K	120°	16.2W	1800lm	F
NC154E-24W/830	220 - 240V	24W	2100lm	3000K	120°	21.6W	2415lm	F
NC154E-24W/840	220 - 240V	24W	2200lm	4000K	120°	21.6W	2520lm	F
NC154E-24W/865	220 - 240V	24W	2300lm	6500K	120°	21.6W	2520lm	F

*Energy efficiency class based on light source lumen

