



LED Panel NP161E - NP164E

Features

- 20W / 40W / 75W LED Panel
- Frosted PC diffuser provide uniform distribution
- Comfort glare-free light
- Good color rendition, Ra ≥ 80

Materials / Finish


- Body: Aluminium frame with white finish
- Diffuser: Frosted PC
- White color

Installation / Mounting

- Quick installation with mounting bracket
- Suitable for recessed mount
- Integral gear unit allows quick and easy installation

Standards


- Designed and manufactured to comply international standard EN60598
- Class II Electrical
- IP 20



(Unit : mm)	(L)	(W)
NP161E	295 x	295
NP162E	595 x	595



(Unit : mm)	(L)	(W)
NP163E	295 x	1195
NP164E	595 x	1195



Model	Voltage	Luminaire Wattage	Driver	Color Temp	Beam Angle	Luminaire Lumen	
NP161E-20W/830	220 - 240V	20W	480mA	3000K	150°	1710lm	F
NP161E-20W/840	220 - 240V	20W	480mA	4000K	150°	1805lm	F
NP161E-20W/865	220 - 240V	20W	480mA	6500K	150°	1900lm	F
NP162E-40W/830	220 - 240V	40W	960mA	3000K	150°	3610lm	F
NP162E-40W/840	220 - 240V	40W	960mA	4000K	150°	3705lm	F
NP162E-40W/865	220 - 240V	40W	960mA	6500K	150°	3800lm	F
NP163E-40W/830	220 - 240V	40W	960mA	3000K	150°	3610lm	F
NP163E-40W/840	220 - 240V	40W	960mA	4000K	150°	3705lm	F
NP163E-40W/865	220 - 240V	40W	960mA	6500K	150°	3800lm	F
NP164E-75W/830	220 - 240V	75W	1700mA	3000K	150°	6650lm	F
NP164E-75W/840	220 - 240V	75W	1700mA	4000K	150°	6745lm	F
NP164E-75W/865	220 - 240V	75W	1700mA	6500K	150°	6840lm	F

EUROPE



INDOOR LUMINAIRE