

Dimmable Filament-LED G80/G95/G125

4.5W/8W/12W


Features

- Extremely energy saving with low power consumption
- Full glass version ideal retrofit of traditional lamps with same appearance / performance / dimensions
- Overall light distribution
- Good color rendition, Ra ≥80



Diagrams

Dimensions:



Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Standards



Applications



Technical Data	
Type of Light Source	
Lighting Technology Used	LED
Non-directional or Directional [NDLS/DLS]	NDLS
Mains or Non-mains [MLS/NMLS]	MLS
Connected Light Source	No
Color tunable light source	No
Envelop [No/Second/Non-Clear]	No
High Luminance Light Source	No
Anti-glare Shield	No
Electrical	
Rated Wattage [W]	4.5W / 8W / 12W
On-mode Power [W]	4.5W / 8W / 12W
Standby Power [W]	N/A
Networked Standby Power [W]	N/A
Rated Voltage [V/Hz]	220-240Vac, 50/60Hz
Power Factor @230V	0.8
Input Current [mA] @230V	24 / 43 / 65
Model	
LED G80 FIL-4.5W-G CL DIM	4.5W
LED G80 FIL-8W-G CL DIM	8W
LED G95 FIL-4.5W-G CL DIM	4.5W
LED G95 FIL-8W-G CL DIM	8W
LED G95 FIL-12W-G CL DIM	12W
LED G125 FIL-4.5W-G CL DIM	4.5W
LED G125 FIL-8W-G CL DIM	8W
LED G125 FIL-12W-G CL DIM	12W
Luminous Flux (Useful Luminous Flux) [lm]	
4.5W	470lm @2700K

8W	800lm @2700K
12W	1520lm @2700K
Performance	
SCDM	<6
Chromaticity coordinates [x, y]	0.463,0.42@2700K
Efficacy [lm/W]	100-127
Color Rendering Index [Ra]	≥80
R9 colour rendering index value	2
Beam Angle [°]	360
Rated Life, Ta@25°C [hrs]	25,000
Lamp Survival Factor	0.9
Lumen Maintenance	0.96
Number of Switching Cycles Before Failure	>15,000
Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	0.5 / 0.5 / 0.7
Flicker Metric [Pst LM]	1
Stroboscopic Effect Metric [SVM]	0.4
Mechanical	
Diameter D [mm]	Φ80 / Φ95 / Φ125
Height H [mm]	115 / 133 / 176
Base	E27 / B22d
Material	Glass
Standard Compliance	
CE-LVD	EN62560
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
CE-EMF	EN62493
Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	F(4.5W, 8W) / E(12W)
Other	
Dimmable [Yes/Only with specific dimmers/No]	Yes
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C
Claim of Equivalent Power, 4.5W [W]	40W
Claim of Equivalent Power, 8W [W]	59W
Claim of Equivalent Power, 12W [W]	99W
Energy Consumption in on-mode [kWh/1000h]	5kWh / 8kWh / 12kWh