



LED Downlight ND341E - ND345E

Features

- 9W / 15W / 20W / 28W / 32W LED Downlight
- Recessed round, uniform distribution
- Ideal replacement up to 70W HID downlight
- Good color rendition, $Ra \geq 80$
- Dimmable as option

Materials / Finish

- Body: Die cast aluminium
- Trim: Die cast aluminium
- Reflector: High purity, anodized aluminium
- Diffuser: Clear Glass



Installation / Mounting

- Quick installation with mounting bracket
- Suitable for recessed mount
- Remote gear unit allows flexible and easy installation
- Cut out dimensions Ø90mm / Ø125mm / Ø145mm / Ø165mm / Ø200mm

Standards

- Designed and manufactured to comply with international standard EN60598
- Class II Electrical
- IP 20

Dimming Options



(Unit : mm)	(D)	(H)	Cut Out Dimensions
ND341E	Ø110	x 42	Ø90
ND342E	Ø140	x 53	Ø125
ND343E	Ø162	x 64	Ø145
ND344E	Ø190	x 76	Ø165
ND345E	Ø230	x 88	Ø200



Model	Voltage	Luminaire Wattage	Driver	Color Temp	Beam Angle	Luminaire Lumen	
ND341E-9W/830	220 - 240V	9W	DC 36±2V C.C. 200mA	3000K	40° / 60°	785lm	F
ND341E-9W/840	220 - 240V	9W	DC 36±2V C.C. 200mA	4000K	40° / 60°	835lm	F
ND341E-9W/850	220 - 240V	9W	DC 36±2V C.C. 200mA	5000K	40° / 60°	885lm	F
ND342E-15W/830	220 - 240V	15W	DC 36±2V C.C. 350mA	3000K	40° / 60°	1310lm	F
ND342E-15W/840	220 - 240V	15W	DC 36±2V C.C. 350mA	4000K	40° / 60°	1360lm	F
ND342E-15W/850	220 - 240V	15W	DC 36±2V C.C. 350mA	5000K	40° / 60°	1410lm	F
ND343E-20W/830	220 - 240V	20W	DC 36±2V C.C. 500mA	3000K	40° / 60°	1745lm	F
ND343E-20W/840	220 - 240V	20W	DC 36±2V C.C. 500mA	4000K	40° / 60°	1795lm	F
ND343E-20W/850	220 - 240V	20W	DC 36±2V C.C. 500mA	5000K	40° / 60°	1845lm	F
ND344E-28W/830	220 - 240V	28W	DC 36±2V C.C. 700mA	3000K	40° / 60°	2445lm	F
ND344E-28W/840	220 - 240V	28W	DC 36±2V C.C. 700mA	4000K	40° / 60°	2495lm	F
ND344E-28W/850	220 - 240V	28W	DC 36±2V C.C. 700mA	5000K	40° / 60°	2540lm	F
ND345E-32W/830	220 - 240V	32W	DC 36±2V C.C. 800mA	3000K	40° / 60°	2795lm	F
ND345E-32W/840	220 - 240V	32W	DC 36±2V C.C. 800mA	4000K	40° / 60°	2840lm	F
ND345E-32W/850	220 - 240V	32W	DC 36±2V C.C. 800mA	5000K	40° / 60°	2890lm	F

