



LED Highbay NH151E - NH154E

Features

- 100W / 150W / 200W / 240W LED Highbay
- Uniformity distribution in high ceiling application
- 120° beam angles for large open area coverage
- Good color rendition, Ra ≥80

Materials / Finish

- Body: Die cast aluminium
- Lens: PC
- Reflector (optional): PC / Aluminium
- Black color

Installation / Mounting

- Pendant mount by chain
- Easy assembly of reflector by screw fixation

Standards

- Designed and manufactured to comply international standard EN60598
- Class I Electrical
- IP 65





Reflector Options




PC 60°
 100W: Ø311 x 166.5mm
 150W: Ø308 x 120mm
 200W: Ø410 x 210.5mm
 240W: Ø410 x 210.5mm



ALU 90°
 100W: Ø340 x 115mm
 150W: Ø370 x 130mm
 200W: Ø430 x 135mm
 240W: Ø430 x 135mm



(Unit : mm)	(D)	(H1)	(H2)
NH151E	Ø250 x	139 x	103
NH152E	Ø250 x	139 x	103
NH153E	Ø250 x	151 x	115
NH154E	Ø300 x	161 x	125



Model	Voltage	Luminaire Wattage	Color Temp	Beam Angle	Luminaire Lumen	
NH151E-100W/830	100 - 277V	100W	3000K	120°	13300lm	D
NH151E-100W/840	100 - 277V	100W	4000K	120°	13775lm	C
NH151E-100W/865	100 - 277V	100W	6500K	120°	14250lm	C
NH152E-150W/830	100 - 277V	150W	3000K	120°	19950lm	D
NH152E-150W/840	100 - 277V	150W	4000K	120°	20665lm	C
NH152E-150W/865	100 - 277V	150W	6500K	120°	21375lm	C
NH153E-200W/830	100 - 277V	200W	3000K	120°	26600lm	D
NH153E-200W/840	100 - 277V	200W	4000K	120°	27550lm	C
NH153E-200W/865	100 - 277V	200W	6500K	120°	28500lm	C
NH154E-240W/830	100 - 277V	240W	3000K	120°	31920lm	D
NH154E-240W/840	100 - 277V	240W	4000K	120°	33060lm	C
NH154E-240W/865	100 - 277V	240W	6500K	120°	34200lm	C

EUROPE



INDOOR LUMINAIRE