



## LED Highbay NH151E - NH154E

### Features

- 100W / 150W / 200W / 240W LED Highbay
- Uniformity distribution in high ceiling application
- 120° beam angles for large open area coverage
- Good color rendition, Ra ≥80

### Materials / Finish

- Body: Die cast aluminium
- Lens: PC
- Reflector (optional): PC / Aluminium
- Black color

### Installation / Mounting

- Pendant mount by chain
- Easy assembly of reflector by screw fixation

### Standards

- ETL





### Reflector Options



**PC 60°**  
 100W: Ø12.20" x 6.56"  
 150W: Ø12.13" x 4.72"  
 200W: Ø16.14" x 8.29"  
 240W: Ø16.14" x 8.29"



**ALU 90°**  
 100W: Ø13.39" x 4.53"  
 150W: Ø14.57" x 5.12"  
 200W: Ø16.93" x 5.31"  
 240W: Ø16.93" x 5.31"



(Unit : inch)	(D)	(H1)	(H2)
<b>NH151E</b>	Ø9.84	x 5.47	x 4.06
<b>NH152E</b>	Ø9.84	x 5.47	x 4.06
<b>NH153E</b>	Ø9.84	x 5.94	x 4.53
<b>NH154E</b>	Ø11.81	x 6.34	x 4.92

Model	Voltage	Wattage	Color Temp	Beam Angle	Lumen
NH151E-100W/830	100 - 277V	100W	3000K	120°	14000lm
NH151E-100W/840	100 - 277V	100W	4000K	120°	14500lm
NH151E-100W/865	100 - 277V	100W	6500K	120°	15000lm
NH152E-150W/830	100 - 277V	150W	3000K	120°	21000lm
NH152E-150W/840	100 - 277V	150W	4000K	120°	21750lm
NH152E-150W/865	100 - 277V	150W	6500K	120°	22500lm
NH153E-200W/830	100 - 277V	200W	3000K	120°	28000lm
NH153E-200W/840	100 - 277V	200W	4000K	120°	29000lm
NH153E-200W/865	100 - 277V	200W	6500K	120°	30000lm
NH154E-240W/830	100 - 277V	240W	3000K	120°	33600lm
NH154E-240W/840	100 - 277V	240W	4000K	120°	34800lm
NH154E-240W/865	100 - 277V	240W	6500K	120°	36000lm

