



LED Highbay NH1020 - NH1024

Features

- 60W / 80W / 100W / 150W / 200W LED Highbay
- Uniformity distribution in high ceiling application
- Separately packed reflectors for cost saving logistics
- 120° beam angle for large open area coverage
- Good color rendition, Ra ≥70

Materials / Finish

- Body: Die cast aluminium
- Lens: PC
- Reflector (optional): PC / Aluminium
- Chips: Lumileds 3030
- Driver: Meanwell / Sosen

Installation / Mounting

- Pendant mount by chain
- Easy assembly of reflector by screw fixation

Standards

- UL, FCC, DLC

Dimming Options




Reflector Options





ALU 90°
Ø17.91" x 5.12"



ALU 120°
Ø19.88" x 4.92"



PC 60°
Ø16.34" x 10.63"



(Unit : inch)	(D)	(H)
NH1020	Ø7.09 x	6.18
NH1021	Ø9.06 x	8.82
NH1022	Ø9.06 x	8.82
NH1023	Ø10.24 x	9.21
NH1024	Ø11.80 x	9.84

Model	Voltage	Wattage	Color Temp	Beam Angle	Lumen
NH1020-3-ALB060-02	90 - 305V	60W	3000K	120°	6800lm
NH1020-3-ALD060-02	90 - 305V	60W	4000K	120°	7200lm
NH1020-3-ALG060-02	90 - 305V	60W	6500K	120°	7500lm
NH1021-3-ALB080-02	90 - 305V	80W	3000K	120°	9000lm
NH1021-3-ALD080-02	90 - 305V	80W	4000K	120°	9800lm
NH1021-3-ALG080-02	90 - 305V	80W	6500K	120°	10400lm
NH1022-3-ALB100-02	90 - 305V	100W	3000K	120°	11400lm
NH1022-3-ALD100-02	90 - 305V	100W	4000K	120°	12200lm
NH1022-3-ALG100-02	90 - 305V	100W	6500K	120°	13000lm
NH1023-3-ALB150-02	90 - 305V	150W	3000K	120°	17500lm
NH1023-3-ALD150-02	90 - 305V	150W	4000K	120°	18500lm
NH1023-3-ALG150-02	90 - 305V	150W	6500K	120°	19500lm
NH1024-3-ALB200-02	90 - 305V	200W	3000K	120°	24000lm
NH1024-3-ALD200-02	90 - 305V	200W	4000K	120°	25000lm
NH1024-3-ALG200-02	90 - 305V	200W	6500K	120°	26000lm