LED Striplight Tunable White

KANDOlite®

* Package Content : ▬ 5m per reel

Features
· Extremely energy saving with low power consumption
· High brightness, multi-functional for linear decoration
· Long average life 30000 hours
· Selective CCT from 2300K to 6500K
· Low thermal output with no IR and harmful UV
· No mercury and hazardous substances
· For all strips with wattage over 14.4W, an aluminium profile
  must be used
· Dimmable as option
· Color Rendering Index: ≥90

Materials / Finish
· Chips : SMD 2016

Installation / Mounting
· Easy to install with 3M adhensive tape, mounting brackets and profile

Standards
· Class III Electrical
· IP20, IP54, IP65, IP67
· UL, ETL

LED Driver Controllers

| 12V/24V LED Driver | LED CCT Controller | LED Touch CCT Controller | LED Remote CCT Dimming Controller |

Connectors

| 4 Pin Quick Connector | Strip-to-Wire | Strip-to-Strip |

| 'I' Type Fast Plug | 'T' Type Fast Plug | Wire-to-Wire Fast Plug |

Profiles

Surface mounted
8
12.2
17

Recessed
8
12.2
17

Unit in mm
* Extra profiles and accessories need to order separately.

IP Structures

1
LED
PCB
10
IP20

2.2
LED
SI Glue
PCB
10
IP54-S

4
LED
SI Tube
PCB
12
IP65

4.8
LED
SI
PCB
12
IP67-R

30,000h SMD IP20 IP54 IP65 IP67 NO UV No INFRA RED c UL us LISTED c ETL us INTERTEK LISTED

Model	Voltage	Wattage	Color Temp	Lumen	PCB Width	Cutting Unit (12V / 24V)	No. of LEDs
LED 2016 9.6W 10-120 TW	9.6W/m	12V / 24V DC	2300-6500K	960lm/m	10mm	50mm/6LEDs / 100mm/12LEDs	120 pcs/m
LED 2016 19.2W 10-240 TW	19.2W/m	24V DC	2300-6500K	1920lm/m	10mm	50mm/12LEDs	240 pcs/m