

LED Ceiling Light NC101E - NC103E



Features

- 14W / 18W / 24W LED Ceiling Light
- Uniform distribution with opal diffuser
- Comfort glare-free light
- Good color rendition, Ra \geq 80

Materials / Finish




- Body: Sheet steel with white finish
- Diffuser: Opaque acrylic

Installation / Mounting

- Suitable for surface mounting
- Integral gear unit allows quick and easy installation

Standards

- Designed and manufactured to comply international standard EN60598
- Class I Electrical
- IP 20, IP44



(Unit : mm)	(D)	(H)
NC101E	Ø260	x 100
NC102E	Ø340	x 105
NC103E	Ø380	x 110



Model	Voltage	Luminaire Wattage	Luminaire Lumen	Color Temp	Beam Angle	Light Source Lumen	ENERGY STAR
NC101E-14W/830	220 - 240V	14W	900lm	3000K	170°	1300lm	F
NC101E-14W/840	220 - 240V	14W	950lm	4000K	170°	1380lm	F
NC101E-14W/865	220 - 240V	14W	1000lm	6500K	170°	1450lm	F
NC102E-18W/830	220 - 240V	18W	1150lm	3000K	170°	1830lm	F
NC102E-18W/840	220 - 240V	18W	1200lm	4000K	170°	1880lm	F
NC102E-18W/865	220 - 240V	18W	1250lm	6500K	170°	1930lm	F
NC103E-24W/830	220 - 240V	24W	1650lm	3000K	170°	2500lm	F
NC103E-24W/840	220 - 240V	24W	1790lm	4000K	170°	2550lm	F
NC103E-24W/865	220 - 240V	24W	1930lm	6500K	170°	2600lm	F

*Energy efficiency class based on light source lumen

EUROPE



INDOOR LUMINAIRE