

LED T8 支架

18W/18Wx2



标准



应用



家居



办公室



购物中心



旅馆



超市



餐厅



停车场



学校



工厂



医院



艺术馆



博物馆



机场



铁路

技术参数

电参数

额定功率 [W]	18W / 18Wx2
额定电压 [V/Hz]	110-130Vac, 50/60Hz
功率因数 @120V	0.9
输入电流 [mA] @120V	167 / 333

佑昌灯光器材有限公司

电话: (852) 2511 0022 传真: (852) 2511 0082 网址: www.prosperitylamps.com 电子邮件: info@prosperitylamps.com

LED	SMD
产品型号	
NL121A-18W/8XX	18W
NL122A-18Wx2/8XX	18Wx2
光通量 [lm]	
18W	1450lm @3000K
	1500lm @4000K
	1550lm @5000K
	1600lm @6500K
18Wx2	2800lm @3000K
	2850lm @4000K
	2900lm @5000K
	2980lm @6500K
光效性能	
色容差	<6
预计每年能源支出 [\$USD]	2.17 / 4.34
光效 [lm/W]	78-89
显色指数 [Ra]	≥80
色效维持 [hr]	>6000
寿命 [yrs] (每日使用3小时)	46
6000小时后, 光通维持率	>0.8
开关测试	>15,000 cycles
启动时间 [S]	<0.5
LED 失效率	<5%
尺寸和物料	
直径 D [in]	Φ2.2
长度 L [in]	48
宽度 W [in]	1.57 / 3.15
物料	Sheet steel, white powder coated
标准	
ANSI	UL8750, UL1993, UL1598, C82.77-2002, C78.377-2008
汞含量 [mg]	0.0
其他	
调光 [Y/N]	N
工作温度	-20° C ~ 50° C
存储温度	-10° C ~ 30° C