

LED 灯带 2016 北美

24W/m



图表

LED驱动控制器:



**12V/24V
LED Driver**



**LED Dimmer
(With Remote
Control Device)**



**LED Manual
Controller**



**LED Remote
Controller**

佑昌灯光器材有限公司

电话: (852) 2511 0022 传真: (852) 2511 0082 网址: www.prosperitylamps.com 电子邮件: info@prosperitylamps.com

©2024 佑昌灯光器材有限公司 保留所有权利

连接器:



4 Pin Quick Connector



Strip-to-Wire



Strip-to-Strip



'I' Type Fast Plug



'T' Type Fast Plug




Wire-to-Wire Fast Plug


铝槽:



Surface mounted




Recessed




* Extra profiles and accessories need to order separately.


尺寸:



IP20



IP54-S



IP67-R

标准



IP20

IP54

IP67

应用



家居



购物中心



旅馆



超市



餐厅



艺术馆



博物馆

技术参数

电参数

额定功率 [W]	24W/m
额定电压 [V/Hz]	100-277Vac, 50/60Hz
功率因数 @120V	0.95
输入电流 [mA] @120V	211
LED	SMD 2016

产品型号

LED 2016 24W 10-240 9XX	24W/m, 12V/24VDC
-------------------------	------------------

光通量 [lm]

24W/m	2040lm/m @3000K
	2100lm/m @4000K
	2160lm/m @6500K

剪断位置 [mm]

24W/m	12.5mm/3LEDs (12V), 25mm/6LEDs (24V)
-------	--------------------------------------

光效性能

色容差	<6
预计每年能源支出 [\$USD]	2.89/m
光效 [lm/W]	85-90
显色指数 [Ra]	≥90
色效维持 [hr]	>6000
光度分布 [°]	120
寿命 [yrs] (每日使用3小时)	27
6000小时后, 光通维持率	>0.8
开关测试	>15,000 cycles
启动时间 [S]	<0.5
LED 失效率	<5%

尺寸和物料

长度 L [mm]	5000 per reel
宽度 W [mm] x 高度 H [mm]	IP20 : 10 x 1
	IP54-S : 10 x 2.2
	IP67-R : 12 x 4.8
	Surface mounted profile : 17 x 8

佑昌灯光器材有限公司

电话: (852) 2511 0022 传真: (852) 2511 0082 网址: www.prosperitylamps.com 电子邮件: info@prosperitylamps.com

	Recessed profile : 17 x 8
LED数目	240 pcs/m
物料	Chips: Epistar
标准	
ANSI	UL8750, UL1993, UL1598, C82.77-2002, C78.377-2008
汞含量 [mg]	0.0
其他	
调光 [Y/N]	Y
工作温度	-20° C ~ 50° C
存储温度	-10° C ~ 30° C